



COMMERCIAL OPERATOR SECTIONAL DOOR CHART

Door Series ▶					Commercial Steel Insulated & Non-Insulated (Square Feet)								Thermospan® (Square Feet)				ThermoMark™ (Square Feet)		Aluminum (Square Feet)	
					216	216 Ins.	220	220 Ins.	2415	2415 Ins.	2411	2411 Ins.	125	150	200	200-20	5150	5200	451	452
					Flush		Ribbed						Insulated				Insulated			
Model	HP	UL LISTED	Mounting Type	Max. Door Weight (Lbs.)	16GA.	16GA. Ins.	20GA. Steel	20GA. Ins.	24GA.	24GA. Ins.	Nominal 24GA.	Nominal 24GA. Ins.	PU-FIP	PU-FIP 1.38"	PU-FIP 2"	PU-FIP 2" 20GA. Ext.	PU-FIP Raised Panel 1.38"	PU-FIP Raised Panel 2"	1/8" Glass 1.38"	1/4" or 1/2" Glass 1.38"
GCL-MT GCL-MJ GCL-MH	1/2	YES	TS	620	170	120	230	160	270	200	300	256	256	256	240	160	256	256	210	144
GCL-T GCL-J GCL-H	1/2	YES	TSC	1120	256	220	370	256	440	340	320	320	256	360	400	300	400	380	360	240
GCL-T GCL-J GCL-H	3/4	YES	TSC	1370	330	256	440	310	530	400	320	320	256	450	450	370	460	440	400	330
GCL-T GCL-J GCL-H	1	YES	TSC	1620	380	280	500	370	570	410	320	320	256	480	480	420	500	480	400	400
GCL-GT GCL-GH	1/2	YES	TSC	1310	300	256	410	280	520	400	320	320	256	430	430	350	450	430	400	320
GCL-GT GCL-GH	3/4	YES	TSC	1450	340	256	450	320	540	410	320	320	256	450	450	400	480	460	400	350
GCL-GT GCL-GH	1	YES	TSC	1650	390	290	510	380	580	410	320	320	256	480	480	420	510	490	400	400
GCL-GH	3	YES	SC	3696	700	500	700	560	770	600	320	320	256	480	900	680	530	680	400	400

- Notes:
- Total door weight, and not the square footage, is the critical factor in selecting the proper operator. Square foot measurements are based on "square doors" (example = 16' x 16').
 - Doors that require special wind-loading and wide doors normally require increased strutting (reinforcement). Strutting doors can significantly increase door weight beyond maximum weight shown. Consult with door customer service for the impact of wind load and strutting on square foot limits.
 - The following doors are roughly equivalent. Square foot values above are based on the doors listed above, but may be applied to the doors below as well.
 - 220 is roughly equivalent to C20
 - 2415 is roughly equivalent to C24
 - 2411 is roughly equivalent to C2400
 - "UL listed" refers to the operator alone, not the operator-door combination
 - Door options such as AFV sections can add significant weight to a door. Consult with the door customer service for the impact of particular options on size limits.
 - For "Commercial Steel Insulated" category, various "backer" options are available. The chart above is based in all cases on the thickest backer available.
 - For "Aluminum Full View" category, various glazing options are available. The chart above is based in all cases on the heaviest glazing available.
 - "PU-FIP" stands for "polyurethane, foamed-in-place." If no notation is present, insulation is "polystyrene laid-in-place."