



- NOTES:
1. PLEASE VERIFY VOLTAGE, PHASE & MOUNTING.
 2. ALL OPTIONAL ARE AT ADDED COST.
 3. A CLEARANCE OF 6" SHOULD BE ALLOWED FOR ACCESS TO ELECTRIC BOX.
 4. CONTROL VOLTAGE IS A NEC CLASS 2 CIRCUIT.
 5. AVERAGE DOOR TRAVEL SPEED IS 8" PER SECOND.

OPEN DRIP-PROOF MOTOR	"A" DIM
1/2HP (1PH)	8 1/8"
3/4HP (1PH)	10 3/4"
1HP (1PH)	10 3/4"
1/2HP (3PH)	8 3/4"
3/4HP (3PH)	9 1/4"
1HP (3PH)	9 3/4"
1/2HP (575V)	8 3/4"
3/4HP (575V)	9 1/4"
1HP (575V)	9 3/4"

TEFC MOTOR	"A" DIM
1/2HP (1PH)	10 1/4"
1HP (1PH)	11 7/16"
1/2HP (3PH)	9 3/4"
1HP (3PH)	10 3/4"
1HP (575V)	10 3/4"

TENV MOTOR	"A" DIM
1/2HP (1PH)	10 1/8"
1/2HP (3PH)	8 13/16"
1HP (3PH)	11 5/16"
1HP (575V)	11 5/16"

ELECTRIC OPERATOR: GCL-GH (HEAVY DUTY) (1/2, 3/4, 1 HP)	
DOOR TYPE:	ROLLING STEEL
MOUNTING TYPE:	FRONT OF HOOD
PROJECT:	
ARCHITECT:	
CONTRACTOR:	
DISTRIBUTOR:	
PLANT:	
DRAWN BY:	DATE:
APPROVED BY:	DATE:
DWG NO.	SHT ___ OF ___
ENG. CERT. NO.	

ARCHITECT DOOR NUMBER	QTY	FACTORY ORDER NUMBER	MOUNT TYPE	VOLTS					PHASE		CONTROL STATION			
				FRONT OF HOOD ROLLING STEEL	115	208	230	460	575	1 PHASE	3 PHASE	3 BTN	KEY SWITCH	EXT. FLUSH 3 BUTTON